

## **SUN ODYSSEY 42I (JEANNEAU)**

Marale II		
Specifications	Overall length	12,85 m
	Hull length	12,59 m
	Waterline length	11,60 m
	Beam	4,13 m
	Displacement light load with deep draft keel	8410 kg
	Standard draft cast iron fin keel with elongated bulb and exterior epoxy barrier coat	2,13 m
	Standard keel weight	2553 kg
	Shoal draft cast iron fin keel with elongated bulb and exterior epoxy barrier coat	1,60 m
cifi	Shoal keel weight	2781 kg
pe	CE category	A9/B10/C14
• • • • • • • • • • • • • • • • • • • •	Architect/designer	M. Lombard
	Water 2 rotomolded tanks located under forward and aft berths with separate deck fills	355 L
	Fuel rotomolded tank located under aft berth with deck fill	130 L
	Holding tank rotomolded tank located in head compartment with valve for overboard discharge	85 L
	via gravity and deck fitting for pump out	100 1
	Fridge fridge compartment with vertical access	180 L
	<b>Furling genoa</b> 122% high-tenacity Dacron cloth, Sunbrella® UV luff protection, Rutgerson® stainless steel eyes	42,4 m2
Sails	Furling mainsail (optional) high-tenacity Dacron cloth, Sunbrella® UV luff protection, Rutgerson® stainless steel eyes	35 m2
	Spinnaker optimal size for boat (not available from Jeanneau)	115 m2
	Total sail area for standard mast and sails	81,5 m2
	Genoa winches 2 x Harken 46.2 self-tailing winches	
	Coachroof winch Harken 40.2 self-tailing winches to port	
	Coachroof winch Harken 40.2 self-tailing winches to startboard	
50	Winch handles 2 x Harken handles with ball-bearing grip	
lin	Line jammers Spinlock, on both sides of coachroof with return blocks	
Sail handling	Mainsheet traveller roof-mounted traveller with ball-bearing cars, control lines lead aft to cockpit	
	<b>Spinnaker deck hardware</b> triple Spinlock jammer to starboard, 5 folding Wichard padeyes on side decks	
	<b>Asymmetrical spinnaker gear</b> halyard, 2 sheets, tack line lead forward on deck, removable bowsprit on foredeck, Harken blocks	
	<b>Symmetrical spinnaker gear</b> halyard, 2 sheets, 2 guys, pole uphaul and downhaul, spinnaker pole and adjustable car for mast, Harken blocks	
	Classic mast aluminium with double spreaders	
Mast and Rigging	Standing rigging discontinuous 1x19 stainless steel wire	
	Backstay fixed	
	Genoa furler with attachment to stemhead fitting and furling line lead aft to roof winch	
	Running rigging polyester topping lift, mainsail halyard, genoa halyard, mainsheet, genoa sheets	
	Rigid boom vang with gas cylinder and control line lead aft to the cockpit	

	Wood inlay on cockpit bench seating	
	Wood cockpit floor inlay	
	Wood side decks hand-laid wooden side decks	
	Cockpit lockers 2 lockers under bench seats and 1 lazerette locker under the port helm seat for	
	technical access to steering system	
	Liferaft locker located un dedicated compartment between helm seats	
	<b>Solid wood cockpit table</b> with all the same functions of the standard table, but with wooden leaves and top Sunbrella® Taupe cover	
	Gas locker located in lazerette locker under starboard helm seat, room for 2 gas bottles with	
iτ	connection to gas system and cut-off valve under stove in the galley	
	<b>Wheels</b> 2 leather-covered steering wheels with compasses at each steering position and stainless steel grabrails	
Cockpit	Emergency tiller delivered with the boat, chrome fitting in cockpit floor	
Co	Steering wheel covers Sunbrella® Taupe with zips for easy removal	
	Instrumentation dedicated space for instruments within easy reach of helm positions, room for	
	GPS chartplotter mounted at aft end of cockpit table with easy viewing from each helm	
	Engine controls throttle and engine control panel mounted at starboard helm, engine panel	
	includes, RPM gauge, warning lights, ignition	
	Swim ladder folding stainless steel ladder mounted on transom	
	Cockpit shower retractable hot and cold water shower with tap	
	Cockpit bimini Sunbrella® Taupe with stainless steel bows, retractable with storage cover	
	Cockpit sprayhood wide Sunbrella® Taupe with vinyl windscreen with zip-out middle window for	
	ventilation, retractable  Anchor locker room for anchor and tackle, integrated windlass area, holder for windlass handle	
	Anchor locker room for anchor and tackie, integrated windlass area, notice for windlass nandle	
	Bow pulpit open, stainless steel	
	Stern pulpits stainless steel with flag holder, buoy bracket	
	Outboard engine bracket mounted on stern pulpit	
	Electric windlass Quick 1000W combination rope and chain, vertical-mounted in the anchor	
	locker, hand-held remote, manual handle  Anchor roller double stainless steel fitting	
are		
	<b>Anchoring kit</b> Delta anchor 20kg with 32 meters of 10mm chain and 45 meters of 18mm line	
Deck Hardw	Lifelines double level of stainless steel lifelines, stainless steel stanchions	
k I	Lifeline gates opening gates on each side	
эөс	Toerail wood profile with 6 integrated stainless steel chocks and drainage for side deck	
7	Wood rubrail for hull protection	
	Cleats 4 x aluminium mooring cleats forward and aft	
	Midship cleats 2 x aluminium cleats placed on side deck near midship chocks	
	Mooring kit 6 fenders and 4 docklines	
	Handrails sculpted, long wood handrails on coachroof for secure movement forward	
	Deck Prisma Process® injected deck, ISO gelcoat surface, discontinuous balsa block coring	
str	Hull solid, hand-laid fibreglass, ISO gelcoat surface, protective barrier coat	
Constr uction	Structure 3rd generation inner fibreglass grid, high-load zones cut out and relaminated, drainage	
<del>- 0 2</del>		
ting	LED navigation lights and anchor light	
	Flush mounted LED chromed brass ceiling lights in saloon, head compartments and cabins	
	Leather-wrapped LED reading lights in forward cabin and aft cabin (s)	
ti	Determed with preducing lights in forward cash and are cash (s)	

y's	Indirect halogen lighting under side decks in saloon and head compartments	
Ligl	Indirect LED lighting under furniture in saloon	
	Gooseneck chart light mounted at nav station	
	12 v alternator output	
Electrical	Charge distributor/isolator	
	Engine start battery capacity, batteries located under aft berths	
	Domestic battery bank capacity, batteries located under aft berths	
	Extra 3 x 110 Ah domestic battery	
	<b>Positive battery</b> switch for engine and domestic bank and general cut-off switch mounted on panel in aft cabin	
	<b>Shorepower 230v</b> inlet with differential breaker, one 230v plug per cabin, 230v plug in galley, saloon and nav station	
	60A battery charger, multi-phase	
	Electrical panel with 12v breakers, 230v breakers, 12v ammeter, 12v consumption meter, 12v charging meter	
	12v plug per cabin and at nav station	
	230v stainless steel microwave, installed in galley cabinet	
	Hot and cold pressurised water distributed through-out the boat via semi-rigid hose	
	"Heavy-duty" water pump and accumulator tank for consistent water pressure	
	<b>40 litre hot</b> water tank that is connected to engine heat exchanger and to 230v electrical system	
	Chromed shower faucets in washrooms	
Bu	Electric bilge pump on float switch and manual dual-action pump in the cockpit	
Plumbing	Digital water level display	
Plu	Shower sumps equipped with individual electric pumps with filters and on-off switches	
	Large manual pump marine toilets	
	Electric Quiet-Flush toilets in each head compartment	
	80 litre holding tank with gravity drain and deck fitting for forward starboard head (port aft	
	50 litre holding tank with gravity drain and deck fitting for forward starboard head (port aft	
	Yanmar 4JH4E 54 HP, 39.6Kw latest generation of environmentally friendly engines	
Sı	Fully soundproofed engine compartment with engine access behind stairwell and from aft	
erii	Stainless steel propeller shaft 30mm diameter	
Ste	Fuel/water separator	
nd .	Built-in muffler, forced air ventilation and stainless steel exhaust fitting aft	
<i>e</i> <b>a</b>	Fixed 3-blade propeller	
zina	Bow thruster installed in a tunnel with dedicated battery	
Engine and Steering	Fibreglass rudder	
	Line cutting collar on shaft for extra protection against fouling	
	Fixed hull ports with track-mounted curtains and shades	4
	Opening cockpit and roof ports	4
and	Lateral fixed windows	6
features and options	Opening deck hatches	7
	Combination shade/insect screens for deck hatches	<i>'</i>
	CD/radio/MP3player in saloon	
7 9	The state of the s	

Comfori	Saloon stereo speakers x 2	
	Cockpit speakers x 2, watertight	
	Air Conditioning 230v 16.000 BTU, vents in saloon and forward cabin and thermostat	
	Forced air heating 1 unit 5500 BTU Webasto® diesel heater installed in stern, vents in aft cabin,	
po	Fine Teak® interior laminated panels with solid wood trim around galley, companionway and	
Wood	Laminate floorboards with light-coloured lines, varnished edges	
	Forward owner's cabin with central berth and storage forward of the berth	
vin	Double berth, with wood trim, high-density foam mattress	2,05 x 1,85 m
cab	Deep cabinet with shelves and hanging rod	1
Foward cabin	White vinyl lining on hull with lateral wood shelf	
Fov	Desk/vanity with leatherette lining and fold-up mirror, reading light and chair with backrest	-
	Private forward head compartment with sink, clothes hook, mirror, towel holder, toilet paper holder,	
	Twin aft cabins	
	Double berths, high-density foam	00 m x 1,48 m
bin	Deep cabinet with shelves and hanging rod per cabin	
Aft cabin	White vinyl lining on hull with lateral wood shelf	
4.	Head compartment aft with sink, separate shower, clothes hook, mirror, towel holder, toilet paper ho	
	Head compartment aft with sink, shower, clothes hook, mirror, towel holder, toilet paper holder, cabi	
Navig ation	Navigation station full-function with general electrical panel, room for the latest in GPS chartplotters	
	Sliding nav desk that can be placed in forward-facing or aft-facing position for increased seating	
	Saloon with U-shaped seating area to starboard, wrap-around cushions and storage under seating ar	ı
	Saloon dining table with wood fiddles, removable pedestal legs	
Saloon	Storage cabinets along hull sides	
	Lounge seating to port with plush cushions and upper storage cabinets	
S	Companionway with wood steps and non-slip strips	
	Plexiglass companionway door with dedicated storage location	
	Galley with double stainless steel sinks with covers, and reversible cutting board, solid countertops,	
×	L-galley to port with glass separator between galley counter and seating area	
Galley	Gimballed 2-burner stove with oven with stainless steel protection bar	
	Single fridge box with freezer area, wire baskets, 12v refrigeration and integrated compressor	
	Single fringe oox with freezer area, wire ouskers, 12v refrigeration and integrated compressor	